

402 Rec'd PCT/PTO 1 25 JUL 2000

REPLACED BY
ART 34 AMDTSystem for coupling the public telephone network to the Internet

The invention relates to a system for coupling the public telephone network to the Internet.

5 Access to the Internet is provided by so-called Internet Service Providers, indicated hereinbelow as ISP. On strategically chosen locations, they have so-called calling points to which their clients, i.e. the Internet users, can call for gaining access to the Internet. The network opera-
10 tor, indicated hereinbelow as NO, provides the traffic of a user to the ISP. The latter chooses the calling points such that people can contact a calling point from practically every telephone connection at local rates.

For explanation of the usual system we refer to the
15 enclosed Fig. 1 in which "nrc 1 - 4" represent the number telephone exchanges and vkc represent traffic telephone exchanges. The designation ISP was already explained above. Subscribers are connected to a number telephone exchange. There, the registration of the calls takes place, which
20 forms the basis for invoicing. A number telephone exchange covers a limited area, in which the areas do not overlap. The traffic telephone exchanges are for connecting subscribers that are connected to different number telephone exchanges.

25 The dialling code is important for invoicing. A number area is a collection of adjacent telephone exchange areas all having the same dialling code. In the following, for the sake of simplicity it has been assumed that a dialling code area only contains one telephone exchange area. For invoic-
30 ing, one employs the term basic area. The basic area is the dialling code area of the user plus all immediately adjacent dialling code areas. With the diagram of Fig. 1, it can be assumed, that the area nrcl is adjacent nrc2 and nrc4. A conversation between nrc3 and nrc4 will be seen as a conver-
35 sation within the basic area and a conversation between nrcl

and nrc3 will be seen as a conversation outside the basic area. It is clear that a conversation between nrc3 and nrc4 will be more expensive for the NO than a conversation between nrc1 and nrc3. However, this is tolerated. The user only looks at the distance "in a straight line" and for the NO, the shortage of income on the conversations between nrc3 and nrc4 is compensated by the extra profits coming from the conversations between nrc1 and nrc3.

However, the latter does not apply to Internet traffic. A calling point of an ISP in nrc3 is called from the areas nrc2, nrc3 and nrc4, but not from nrc1. For the latter, a different calling point has been arranged. In all, an ISP in the Netherlands needs 26 calling points for national coverage.

Such a system has a number of disadvantages:

- a) the NO must provide services at a low rate, even if the traffic is handled as interlocal traffic;
 - b) Internet traffic in which the user and the ISP are connected to two different NOs involves much costs and little profits.
 - c) Internet traffic can not be distinguished from the other traffic, as a result of which the trend determination can not be established directly from traffic measurements, which makes network planning for the NO more difficult;
 - d) Internet traffic is difficult to predict and in case of overload or failure of a calling location, a domino effect may occur, as will be explained further;
 - e) it is necessary to have a large number of calling points for obtaining national coverage, this also in the areas where little traffic is to be expected;
 - f) all calling points must have a number of their own and those numbers must be communicated to the users;
 - g) combining the common telephone costs and the Internet costs is very expensive and is therefore hardly applied.
- Said domino effect could arise as follows. A user in

Almere can gain access to his ISP at a local rate in Lelystad, Amersfoort or Amsterdam.

Now if the calling point Lelystad can not be contacted as result of a failure, a number of users will contact 5 Amersfoort and others will contact Amsterdam. There, this may give rise to difficulties, so that users from Amsterdam or Hoofddorp will contact Haarlem, for example. This causes an extra loading of the network between various telephone exchanges and extra loading at the calling points. This 10 results in the so-called domino effect as a result of which the ISP may become inapproachable and congestion will arise in the telephone exchange.

The object of the invention is to remove the difficulties described above and to that end the invention provides 15 for that a special number sequence is determined for the ISPs and that a specific number from the sequence is assigned to a specific ISP.

For the Netherlands in particular, a number sequence 067xxx can be contemplated.

20 A 067xxx-call can now be led to an ISP across the shortest trajectory possible, which is to be judged by the NO.

In Fig. 2 the system according to the invention is indicated diagrammatically. The employed terms correspond to 25 the ones applied in Fig. 1 so that they need not be explained further. Per vkc, one access to an ISP is established. From the vkc, all Internet traffic is directly led to the calling point of the ISP, which calling point may also be coupled to an underlying number telephone exchange.

30 This provides great advantages for both parties. For the NO: for Internet traffic which was already within the same vkc-area, nothing will change. For traffic which in the existing situation is led from the one vkc to the other, one saves a telephone exchange passage and a connection in 35 the network between the vkc's.

09600982-091400

For the ISP: the number of calling points can be reduced, e.g. from 26 to 20.

By using the specific number sequence, a calling point can always be contacted per vkc at a low rate. According to 5 the present regulations in the Netherlands the sequence 067xxx is destined for "videotext and data services", so that according to the invention said sequence is most suitable for that purpose. The routing tables can now be set such, that in the areas nrcl, nrc2 and nrc3 the number 10 067xxx refers to ISP (a) and in the area nrc4 the same number refers to ISP (b). Invoicing said number is independent from the location of ISP (a) or ISP (b).

At the same time, with the system according to the invention it is achieved, that an ISP requires only one 15 number which is valid nationwide. Thus, the Internet users need not remember various numbers for e.g. at home and at the office. The system according to the invention has the additional advantage of a nationwide valid rate per ISP, with all Internet traffic now being easily recognizable, so 20 that this can be taken into account on dimensioning the network.

NO and ISP can make an arrangement on how to act in case of calamities, such as failure of a calling point. Users can no longer move directly to other calling points 25 since they have no control over the choice of calling point. It would be possible to redirect the traffic in a controlled way behind the scenes. This can be done by both the NO and the ISP.

On applying the invention, combining the costs of NO 30 and ISP is possible in a simple way. However, NO can continue settling up the telephone traffic and ISP can continue settling up the use of Internet in the usual way. Another possibility is that NO makes the number available to the users free of charge and settles up with the ISP. For the 35 NO, the advantage is in the reduction in invoice lines, a decreased collection risk and a better use of the network.

09600982 091400

For the ISP it is possible to provide actual unlimited access to the Internet at a slightly higher rate. This further depends on the rates to be paid, for that matter.

In particular for occasional users it can be advantageous that the NO bills both the telephone traffic and the use of Internet. For users who use the Internet for e.g. only an hour per month, a subscription is relatively expensive so that an "open entry" is cheaper. Then one need not check in and subscribe in advance. At the moment, those users are of no interest for the ISP. They are anonymous and the costs of measuring and billing count for little compared to the returns.

It will be obvious that only one possible embodiment of a system according to the invention has been illustrated in the drawing and described above and that many changes can be made without leaving the inventive idea as it is indicated in the enclosed claims.

- claims -

09600982-091400